

Smartlivestock: An Efficient CNN-Based Approach for Automated Cattle Breed Identification

MOKKALA KIRAN MONI,

Assistant Professor, Department of CSE
Annamacharya Institute of Technology And Sciences,
Tirupati-517520, A.P
kiranmonireddy@gmail.com

TANDERI VISHNU PRIYA,

UG Scholar, Department of CSE
Annamacharya Institute of Technology And Sciences,
Tirupati-517520, A.P
priyapriya125sss@gmail.com

PRASADAM SUPRIYA,

UG Scholar, Department of
CSE
Annamacharya Institute of
Technology And Sciences,
Tirupati-517520, A.P
supriyapvr@gmail.com

MANDLA YASWANTH

RAHUL,
UG Scholar, Department of CSE
Annamacharya Institute of
Technology And Sciences,
Tirupati-517520, A.P
yaswanthrahul143@gmail.com

BEEGALA VENKATA

HARSHAVARDHAN,
UG Scholar, Department of CSE
Annamacharya Institute of Technology
And Sciences,
Tirupati-517520, A.P
bharsha11567@gmail.com

Abstract -- Accurate cattle breed identification plays a vital role in modern livestock management by supporting genetic preservation, efficient breeding practices, and improved productivity. Although deep learning techniques have shown strong performance in image-based classification tasks, many existing approaches primarily emphasize accuracy under controlled conditions, with limited focus on real-world deployment. This paper presents a Visual Intelligence Framework for automated cattle breed recognition using a transfer learning approach based on the MobileNetV2 convolutional neural network. The proposed system integrates image preprocessing, deep feature extraction, and a confidence-based prediction mechanism to enhance robustness under varying environmental conditions such as lighting, background complexity, and pose variations. In addition to model performance, the framework prioritizes computational efficiency and deployment feasibility. A web-based interface is developed to enable real-time interaction with the trained model. Experimental results demonstrate that the system achieves reliable classification performance with low computational overhead, making it suitable for practical livestock monitoring applications.

Keywords -- Cattle breed classification, deep learning, transfer learning, MobileNetV2, image-based recognition, smart livestock management, agricultural AI.

I. Introduction

Cattle breed recognition plays a crucial role in modern livestock management by enabling informed breeding decisions, preserving genetic diversity, and improving overall productivity. Accurate identification of cattle

breeds allows farmers and livestock managers to monitor herd composition, maintain breed purity, and support effective farm management practices. Nevertheless, conventional approaches to identification are very manual-labor-intensive; they are also subjective and cannot be scaled in large or dynamic farms. The latest computer vision and deep learning developments have presented automotive substitutes to visual recognition processes. This is especially true of Convolutional Neural Networks (CNNs) which have been shown to be capable of learning discriminative visual features directly off the images. Their hierarchical nature in extracting features enables models to not only extract low-level features, such as, edges and textures, but also high level semantic features, such as, body structure and appearance. These characteristics render the CNN-based methods desirable to the cattle breed recognition. Photos that are taken in the farm settings are known to have an inconsistency in lighting, the complexity of the background, the body position, and the quality of the picture. This variability may decrease prediction confidence and restrict the practical utility of typical classification pipelines. In order to overcome such difficulties, this paper introduces a Visual Intelligence Framework of automated breed recognition of cattle using transfer learning. The suggested system utilizes a lightweight MobileNetV2 network to obtain deep visual features at a low cost and with minimal computation. The framework does not emphasize the complexity of models but system-level robustness and deployability. The given methodology is aimed to serve in the field of practice-based livestock management situations where breed prediction can be automated, more reliable, and interpretable.

II. Literature Survey

Computer vision and deep learning techniques have significantly advanced cattle identification systems in recent years. Early advancements in object detection, such as YOLO-based models, improved real-time detection accuracy and efficiency in complex environments [1]. Traditional machine learning approaches like Random Forest and boosting algorithms such as XGBoost have also contributed to classification tasks by improving prediction accuracy and reducing errors [2], [3].

To address data scarcity and adaptability challenges, meta-learning approaches were introduced, enabling models to quickly adapt to new datasets with minimal training samples [4]. In parallel, multi-modal approaches combining depth and RGB data improved robustness in livestock identification by capturing both texture and structural features [5].

Region-based deep learning models such as Mask R-CNN and Faster R-CNN further enhanced object detection and segmentation performance, enabling accurate identification in crowded herd environments [6], [12]. Deep convolutional architectures like ResNet improved feature learning by addressing vanishing gradient issues, while large-scale CNN models demonstrated strong performance in image classification tasks [7], [8].

Biometric approaches, such as muzzle pattern recognition, were proposed as non-invasive alternatives, providing reliable identification without stressing animals [9]. Additionally, CNN-based image feature extraction methods enabled effective cattle breed classification by capturing discriminative visual characteristics [10], [11].

Metric learning approaches, such as FaceNet, introduced embedding-based identification techniques, allowing models to distinguish between individual cattle in unconstrained environments [13]. Deployment-focused research emphasized scalable solutions using cloud-based platforms for managing and deploying deep learning models in agriculture [14].

More recently, real-time cattle identification systems using YOLO-based deep learning models have demonstrated improved performance in practical farm conditions, enabling efficient and automated livestock management [15].

III. Methodology

The proposed Visual Intelligence Framework for automated cattle breed recognition utilizes a deep learning-based approach to achieve reliable classification in real-world agricultural environments. It combines image preprocessing, transfer learning-based feature extraction, probabilistic classification, and performance evaluation into a unified pipeline. The workflow follows a sequence of stages that convert raw cattle images into accurate breed predictions.




Fig. 1. System architecture of the proposed transfer learning-based cattle breed classification framework.

A. Data Collection and Dataset Description

The dataset consists of labeled cattle images belonging to five breed categories: Jersey, Red Dane, Holstein Friesian, Ayrshire, and Brown Swiss. Images are captured using standard digital cameras or mobile devices, resulting in variations in illumination, background complexity, pose, and viewing angle. This data diversity ensures that the model learns robust visual representations suitable for practical farm environments rather than controlled laboratory settings.




Fig. 2. Sample dataset images of selected cattle breeds for deep learning-based classification.

B. Data Preprocessing and Normalization

To ensure compatibility with the deep learning model, all input images are resized to a fixed spatial resolution.

Pixel intensity normalization is applied to scale image values into a uniform range, improving numerical stability and convergence during training. Image normalization is expressed as:

$$I' = \frac{I}{255}$$

where I denotes the original image and I' represents the normalized image. This preprocessing step reduces the impact of lighting variations while preserving important visual features such as coat texture and body structure.

C. Transfer Learning-Based Feature Extraction

The main core feature extraction is carried out with the help of a Convolutional Neural Network (CNN) whose weights are pre-trained. Transfer learning approach is used instead of training the network directly and using already trained generic visual patterns of edges, contours and textures. The convolutional layers are trained in advance and kept as fixed feature extractors which makes it efficient to learn at low computational cost.

The feature extraction process is mathematically represented as:

$$F = f_{\text{CNN}}(I')$$

where $f_{\text{CNN}}(\cdot)$ denotes the convolutional feature extraction function and F represents the high-level feature vector obtained from the normalized input image.

D. Breed Classification and Decision Making

The feature vector that has been extracted will be sent to fully connected layers, which will do the multi-class classification. A softmax activation is provided to produce probability scores on the possible classes of cattle breed. This softmax can be characterized as:

$$P(y_i | F) = \frac{e^{z_i}}{\sum_{j=1}^C e^{z_j}}$$

where C represents the total number of breed classes and $P(y_i | F)$ denotes the predicted probability for class i . The breed corresponding to the highest probability value is selected as the final prediction.

E. Training Strategy and Performance Evaluation

The model is optimized with respect to a labeled image to train it. The training is done repeatedly among epochs to enable the network to acquire discriminative breed-specific features. The model performance is measured using the training and validation data in order

to determine the ability to learn as well as the generalization performance. The accuracy of the classification is calculated as:

$$\text{Accuracy} = \frac{\text{Number of Correct Predictions}}{\text{Total Number of Samples}} \times 100$$

The experimental results demonstrate strong learning behavior, with high training accuracy and reasonable validation accuracy under diverse image conditions.

F. Result Generation and Analysis

In inference, the trained model takes unseen images of cows and gives a predicted breed and a probability score. Through this probabilistic output, the confidence interpretations of the results are achievable, and as a result predictions made, which are applicable even in the real-world livestock monitoring situations.

G. System Design Significance

In contrast to the traditional framework of stationary image classification models, the offered methodology is built on the focus of robust features learning, computational efficiency and deployment preparedness. Transfer learning, probabilistic classification plus systematic evaluation allows proper recognition of cattle breeds and remains practical in terms of application to the agricultural world.

The framework uses a Convolutional Neural Network (CNN) which is built on the MobileNetV2 scheme as the underlying classification algorithm. MobileNetV2 is chosen because it has a lightweight architecture, depthwise separable convolutions, and is applicable to install on resource-constrained devices. MobileNetV2 is capable of reaching a compromise between computational efficiency and accuracy, which is unlike heavyweight CNNs and suitable in real-time applications to agriculture.

Transfer Learning Approach

The given system uses transfer learning in order to avoid the possibility of training a deep network on the initial level. It uses a MobileNetV2 model that is pre-trained on a large-scale image database as a feature extractor. The trained convolutional layers store learnt representations of general visual patterns like edges, contours and textures. This training just freezes these layers and new classification layers are also trained in order to identify cattle breeds. This plan saves time on training and enhances in generalization.




Fig. 3. Transfer learning workflow for deep CNN-based cattle breed classification using MobileNetV2.

IV. Results and Discussions

The proposed Visual Intelligence Framework for Automated Recognition of Cattle Breeds was evaluated using a deep learning model trained over 20 epochs. The performance analysis focuses on classification accuracy, generalization behavior, and practical reliability under real-world conditions.

A. Model Accuracy Assessment

The training accuracy of the MobileNetV2-based model was 98% which reflects the effective learning of such visual features of the breed specificity like the coat texture, body structure and shapes pattern. The training accuracy is high, which proves that transfer learning can be effective in the recognition of breeds of cattle when there is a small amount of training data.

The validation score was found to be 71 percent, indicating how difficult it is to work with unconstrained agricultural images. Disagreements in lighting, cluttered background, variation in posture, and visual relatedness between different breeds of Jersey and Brown Swiss influence reduced validation performance. This level of accuracy can be regarded as reasonable when applied to the real-life situations with livestock, as images are taken when the conditions are non-uniform.

Fig. 4. Table Representing Training and Validation Accuracy

Metric	Value
Number of Cattle Breeds	5
Training Epochs	20

Training Accuracy (%)	98.14
Validation Accuracy (%)	69.87




Fig. 5. Comparison of training and validation accuracy for the proposed cattle breed classification model.

B. Performance Gap Analysis

The gap between the training and the validation accuracy is observed to be a result of moderate overfitting. This is however to be expected when working with deep models when the data to be trained on are relatively small. The system incorporates a confidence-sensitive decision mechanism to reduce the effects of prediction uncertainty; however, during deployment, low-confidence results are suppressed, and the system is expected to be more reliable.

C. System Performance and Efficiency

It is contrary to the benchmark-based research in which the values of absolute accuracy are not as important as the robustness of systems and their deployment feasibility. MobileNetV2 architecture is also lightweight and thus the system is applicable in the web based and resource-constrained environments because of the low computational overhead. The integration of preprocessing, feature extraction, classification, and visualization of results allows showing the possibility of using deep learning models in practice in managing livestock.

D. Future Research Directions

In as much as the framework is effective, there are limitations to it. By using bigger datasets and more varied data, using multi-view images, or data

augmentation methods, the classification performance of visually similar breeds can be further enhanced. It could also be done in the future to investigate the fine-tuning of deeper layers of the network and incorporating time-based information and picture sequences to improve stability in the prediction.

E. Summary of Findings

The findings have shown that although perfect generalization is hard to achieve in real world, the presented system gives reliable and explainable predictions that can be useful in making decisions. The transfer learning approach and the concept of confidence-aware classification allow the system to align the precision and realistic application. This means that additional refinements in the future (e.g. increasing the size of the dataset and more sophisticated regularization methods) should lead to a further enhancement of validation performance.

V. Conclusion

The intended audience of this paper was given a Visual Intelligence Framework of Automated Recognition of Cattle Breeds that will be applied to the practical environment of livestock. The framework combines lightweight deep learning with system-level intelligence to make credible identification of the breed when no constraints are provided on imaging. Using a convolutional neural network based on the transfer learning of MobileNetV2, it can successfully extract The gap between the training and the validation accuracy can be seen as a consequence of moderately good overfitting. This is of course likely to occur when dealing with deep models in situations when the data which is to be trained on are very small. The system will use a confidence-sensitive decision mechanism to minimize the impact of uncertainty in prediction but, when deployed, the results with low confidence are suppressed, making the system more plausible.

Discussion

The results have demonstrated that it is not extremely easy to make perfect generalization in real world, but the presented system provides predictions that are reliable and explainable and can be utilized during decision making. The concept of confidence-aware classification coupled with the transfer learning approach can enable the system to match the precision and application realism. It implies that further improvements of the algorithm in the future (e.g. making the data size bigger

and more intricate regularization techniques) will result in another improvement of validation performance. computational complexity. It is also featured with adaptive preprocessing and confessional classification method, which enhance the reliability of predictions by discouraging the uncertainty results that are crucial in practice in agricultural application. Experimental results illustrate that the proposed framework had an excellent training performance and decent validation accuracy with experimental on a variety of cattle breeds. All in all, the article provides an insight into how deep learning and sound system structure should be interconnected as the entire work implicates the implication of transferring cattle breed detection out of the closed research environment and into the environment of livestock management tools accessible to non-technical clients.

References

- [1] A. Bochkovskiy, C.-Y. Wang, and H.-Y. M. Liao, "YOLOv4: Optimal speed and accuracy of object detection," *arXiv:2004.10934*, 2020.
- [2] L. Breiman, "Random forests," *Mach. Learn.*, vol. 45, no. 1, pp. 5–32, 2001.
- [3] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowl. Discov. Data Min.*, 2016, pp. 785–794.
- [4] C. Finn, P. Abbeel, and S. Levine, "Model-agnostic meta-learning for fast adaptation of deep networks," in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2017, pp. 1126–1135.
- [5] Y. Guo, L. Zhang, H. Liu, and J. Wang, "Point cloud-based livestock identification using Siamese networks," *Pattern Recognit.*, vol. 110, Art. no. 107118, 2021.
- [6] K. He, G. Gkioxari, P. Dollár, and R. Girshick, "Mask R-CNN," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, 2017, pp. 2961–2969.
- [7] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2016, pp. 770–778.
- [8] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "ImageNet classification with deep convolutional neural networks," *Commun. ACM*, vol. 60, no. 6, pp. 84–90, 2017.

- [9] S. Kumar, A. Pandey, and S. K. Singh, “Biometric cattle identification using muzzle point pattern,” *Comput. Electron. Agric.*, vol. 128, pp. 44–53, 2016.
- [10] S. Kumar and R. Singh, “Non-invasive livestock identification using deep learning: A review,” *Artif. Intell. Agric.*, vol. 8, pp. 1–12, 2023.
- [11] H. Q. Nguyen, T. T. Nguyen, T. V. Tran, and T. H. Pham, “Cattle identification using deep CNN features,” *Sensors*, vol. 18, no. 9, Art. no. 2879, 2018.
- [12] S. Ren, K. He, R. Girshick, and J. Sun, “Faster R-CNN: Towards real-time object detection with region proposal networks,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 39, no. 6, pp. 1137–1149, 2017.
- [13] F. Schroff, D. Kalenichenko, and J. Philbin, “FaceNet: A unified embedding for face recognition and clustering,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2015, pp. 815–823.
- [14] P. Voigt and A. von dem Bussche, “Cloud-based annotation and deployment of deep learning models for agriculture,” *IEEE Access*, vol. 9, pp. 112345–112356, 2021.
- [15] Y. Zhang, H. Li, and X. Wang, “Real-time cattle identification using YOLO-based deep learning models,” *Comput. Electron. Agric.*, vol. 210, Art. no. 107118, 2024.